# **HYDRO GOLD SERIES**

TECHNICAL SPECIFICATIONS	
Drain	End drain
Pump Location(s): Select 1	Std. = Standard / Alt LF/RF Optional
Bath Weight (empty)	140 lbs
Gallons to Operate	30-48
ELECTRICAL SPECIFICATIONS	
Motor/Pump	(1) 115v 20AMP GFCI Circuits

BATHERS: 1	
INSTALLATION	
	DECK (D)
	UNDER MOUNT (U)
·	ALCOVE (A)
	FREESTANDING (F)
	CLAWFOOT (L)
	PEDESTAL (P)



# STANDARD FEATURES & ACCESSORIES for HYDRO GOLD SERIES BATHS

(1) 115v 20AMP GFCI Circuit

12 Water Massage Jets Back Massage System(s) (6 Jets) Accumassage Back and Neck Jets ⊕ 6 Ultra Flow Jets - ( )-

Inline Stainless Steel Heater

### **PUMPS**

3.25 Hydropower 3-speed Pump Quiet Pad Anti-Vibration Mounted Pump

#### **HEATERS**

Stainless Steel Electric Heater

#### **CONTROLS**

Air Switch On/Off Control(s) For Hydro Pump & Mood Light 3 Speed Massage: High, Medium or Low

HydroClean Water Purity System HydroCleanse

## STANDARD ACCESSORIES

Mood Light

Lift & Turn Drain - White, Biscuit, Bone, Brushed Nickel, Oil Rubbed Bronze, Polished Chrome

Deluxe Cushion Pillow

EZ Level Adjustable Legs

FDA Recipe Non-Toxic Food & Beverage Grade Plumbing (primarily) 30 Point Quality Assurance Factory Test

### REQUIREMENTS

Pump Locations: Select 1

Electrical: two 115v 20AMP GFCI Circuits

Drain: Select Color / Finish

Tub should not be supported by the lip in any way.

Level tub & screw or glue EZ Level adjustable legs to sub floor. **CUT OUT DIMENSIONS:** 

**OVALS:** A template will be provided


**RECTANGLES:** Subtract 1" to 1.5" from length & width for hole


**EZ CLEAN CAST ACRYLIC** LIMITED LIFETIME WARRANTY




# **OPTIONAL FEATURES & ACCESSORIES**

(Please type in the box below)







**INSTALLATION WILL NOT REQUIRE MORTAR BEDDING** 

Some standard & most alternate pump locations may stickout past perimeter of the bath 1"-3". NOTE: Graphics may not be to scale. Specifications and features are subject to change without notice and are ± .25". All final measurements should be taken from tub on site.

Access 18"x 18" or larger is required for each pump. Consult your contractor for installation requirements.