FV-20VQ3_SpecSheet



WhisperCeiling[™] 190 CFM Ceiling Mounted Fan

FV-20VQ3

• MORE DETAILS	• Air Volume (CFM) 190 (144 at 0.25" static pressure)
	• Noise (sones) 1.3
	• Power Consumption (Watts) 42 (42 at 0.25" static pressure)
	• Energy Efficiency (CFM's/Watt) 4.5 (4.1 at 0.25" static pressure)
	• Speed (RPM) 696 (871 at 0.25" static pressure)
	• Current (Amps) 0.35 (0.35 at 0.25" static pressure)
	• Power Rating (V/Hz) 120/60
	• Motor Type Condenser
	• Type of Motor Bearing Ball
	• Thermal Fuse Protection Yes
	• Blower Wheel Type Sirocco
	• Duct Diameter (inches) 6"
	• Mounting Opening (inches sq.) 12 3/16"
	• Grille Size (inches sq.) 15"
	◦ SmartAction [™] Motion Sensor No
	◦ CustomVent [™] Variable Speed Control No
	• SmartFlow TM Optimum CFM Technology No
	• Light No
	• UL Listed for Tub/ Shower Enclosure Yes, when used with a GFCI branch circuit wire
	• Washington State VIAQ Code Yes
	• Mfg in ISO 9001 Certified Facility Yes
	• Super Quiet Operation Yes

- Energy Star Qualified Yes
- Totally Enclosed Condenser Motor Yes, for long life Rated for continuous run

.....

.....

.....

- Easy Installation Yes
- Rust Proof Paint Treatment Yes, on galvanized housing
- Built-In Damper Yes, to prevent back draft
- Contemporary Grille Design Yes
- Weight 17.2 pounds

• **UPC**092281134499

.....